



技术参数:

- 插芯:
- 插针数: 25
 - 额定电流: 4A
 - 额定电压: 50V
 - 额定脉冲电压: 0.8kV
 - 污染等级: 3
 - 绝缘阻抗: $>10^{10}\Omega$
 - 材料: 聚碳酸酯
 - 颜色: RAL 7032 (浅灰色)
 - 温度范围: $-40^{\circ}\text{C} - +125^{\circ}\text{C}$
 - 依据UL 94的阻燃等级: V0
 - 可插拔次数: >500
- 插针:
- 接线方式: 冷压连接
 - 材料: 铜合金
 - 表面处理: 镀银
 - 接触电阻: $<3\text{m}\Omega$
 - 线径范围: $0.09-0.82\text{mm}^2(28-18\text{ AWG})$

Technical specification:

- Insters:
- No. of contact: 25
 - Rated current: 4A
 - Rated voltage: 50V
 - Rated impulse voltage: 0.8kV
 - Pollution degree: 3
 - Insulation resistance: $>10^{10}\Omega$
 - Material: polycarbonate
 - Colour: RAL 7032(light grey)
 - Temperature range: $-40^{\circ}\text{C} - +125^{\circ}\text{C}$
 - Flammability acc.to UL 94: V0
 - Mating cycles: >500
- Contacts:
- Terminal: crimp terminal
 - Material: copper alloy
 - Surface: hard-silver plated
 - Contact resistance: $<3\text{m}\Omega$
 - Wire gauge: $0.09-0.82\text{mm}^2(28-18\text{ AWG})$

| | | | |
|--|--------------|----------------|---------------|
| | | 订货号 Order No. | |
| | | 产品代号 Part Code | |
| 版本 REV | 重量 weight | 比例 Scale | SO-HMD-012-MC |
| V1.0 | 9.1g | 1:1 | |
| 浙江思美克电气科技有限公司 ZHEJIANG SMICO ELECTRICAL TECHNOLOGY CO.,LTD | | | |