



技术参数:

插芯:

- 插针数: 8+PE
 - 额定电流: 10A
 - 额定电压: ~50V/-250V
 - 额定脉冲电压: 0.8kV
 - 污染等级: 3
 - 依据UL/CSA的额定电压: 50V
 - 额定电压(直流电压): 120V
 - 绝缘阻抗: $>10^{10}\Omega$
 - 材料: 聚碳酸酯
 - 颜色: RAL 7032(浅灰色)
 - 温度范围: $-40^{\circ}\text{C} - +125^{\circ}\text{C}$
 - 依据UL 94的阻燃等级: V0
 - 可插拔次数: >500
- 插针:
- 接线方式: 冷压连接
 - 材料: 铜合金
 - 表面处理:
 - 镀银
 - 镀金
 - 接触电阻: $<3\text{m}\Omega$
 - 线径范围: $0.14-2.5\text{mm}^2(26-14\text{ AWG})$
 - 工具:
 - 冷压钳: TL02G
 - 退针器: TL00

Technical specification:

Inserts:

- No. of contact: 8+PE
 - Rated current: 10A
 - Rated voltage: ~50V/-250V
 - Rated impulse voltage: 0.8kV
 - Pollution degree: 3
 - Rated voltage acc.to UL/CSA: 50V
 - Rated voltage(direct voltage): 120V
 - Insulation resistance: $>10^{10}\Omega$
 - Material: polycarbonate
 - Colour: RAL 7032(light grey)
 - Temperature range: $-40^{\circ}\text{C} - +125^{\circ}\text{C}$
 - Flammability acc.to UL 94: V0
 - Mating cycles: >500
- Contacts:
- Terminal: crimp terminal
 - Material: copper alloy
 - Surface:
 - Hard-silver plated
 - Hard-gold plated
 - Contact resistance: $<3\text{m}\Omega$
 - Wire gauge: $0.14-2.5\text{mm}^2(26-14\text{ AWG})$
 - Tools:
 - Crimp contact tool: TL02G
 - Contact removal tool: TL00

标记/Mark	数量/Number	变更描述/Description		签名/Signature	日期/Date	表面处理/Finish					图号/Drawing No.	
						材料/Material					产品代号/Part Code	
						比例/Scale	版本/REV.	重量/Weight	数量/Qty.			产品料号/Part No.
						姓名/Name		日期/Date				产品名称/Part Name
绘图/Drawn	BQ LUO	18.10.2010	标准化/Stand.	-	-	1:1	V1.0	7.6g	-			-
审核/Checked	P RAO	18.10.2010										-
工艺/Process	-	-	批准/Approved	YY LIN	18.10.2010							-
						All Dimensions in mm Original Size DIN A 4				浙江思美克电气科技有限公司 ZHEJIANG SMICO ELECTRIC TECHNOLOGY CO.,LTD		